

TECHNICAL DATA SHEET



Name of Carpet	40 MM MY GREEN PATH.7200+4400-12.5/16	Tolerances
Tufting Type & Infill	"5/16 inch" cut pile, sand filled artificial turf	
Grass yarns	%100 PE Monofilament, UV Resistant, RR7200.8 Straight + 4400/4 Green Curly PP	
Dtex of Yarn	7200+4400	
Primary backing	100% Polypropylene UV-stablized, appr.165 gr/m ² single	
Coating	Carboxylated (SBR) German Origin Latex appr. 1415 gr/m ² with 5 mm perforation water holes	
Pile height	40mm	±1mm
Total thickness	42mm	±1mm
Stitches per 10cm	12 Pcs	±%1
Number of tufts/ m ²	15120 Pcs	± %1
Pile weight	1330 g/ m ²	± %3
Backing weight	165 g/ m ²	± %2
Total weight	2910 g/ m ²	± %3
Roll width	4.00m	±%1cm (with or without edging)
Roll length	According to installation schedule & based on purchase order	
Water permeability	60lt/m ² per minute	
Color fastness	According to the highest standards, DIN 54004 (min 7) approved	
UV – stability	According to the highest standards 6000 hrs Weather -0-Meter Test, based on DIN 53387	
Infill Materials	Non-infill (Only 7 Kg silica sand per m ²)	
Warranty	7 Years	

الإدارة : أول طريق مصر إسكندرية الصحراوي خلف فندق الواحة ، رقم 1 قبلا النجار
المصنع : محافظة السويس ، مدينة شمال خليج السويس ، منطقة توسعات عتاقة الصناعية

www.scoregrass.it info@scoregrass.it

+202 35320528 - +202 35320529