

New Unica - cable outlet - 2 modules - clip-in - white

NU386218

Range	New Unica
Accessory / separate part category	Cabling accessory
Product or component type	Cable outlet
Device presentation	Mechanism
Number of modules	2 modules
Fixing mode	Clip-in
Colour tint	White (RAL 9003)

Complementary

Rated current	16 A
Connections - terminals	Cable
Number of cables	1 12 mm² for flexible 1 12 mm² for rigid
Material	Thermoplastic ABS-UV stabilised: mechanism cover
Standards	EN 60670-22 CE
Directives	2014/35/EU - low voltage directive
Ambient air temperature for operation	1530 °C
Ambient air temperature for storage	035 °C
Width	45 mm
Height	45 mm
Net weight	0.021 kg

Resistance to chemical agents Resistant to alcohol (70 %)

Resistant to alcohol (96 %)

Resistant to A-Lactic Acid

Resistant to diluted quaternary ammonium

Resistant to diluted bleach Resistant to diluted ammonia Resistant to soapy water Resistant to crystal cleaner

Resistant to hydrogen peroxide 10 volumes

Resistant to hexane

_	:				_	1
-	nvi	rn	n	m	Δ	nt
_					v	

IK degree of protection	IK04
IP degree of protection	IP20

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.5 cm
Package 1 Width	4.5 cm
Package 1 Length	4.5 cm
Package 1 Weight	22.0 g
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	8.5 cm
Package 2 Width	18.0 cm
Package 2 Length	18.5 cm
Package 2 Weight	308.0 g
Unit Type of Package 3	S03
Number of Units in Package 3	80
Package 3 Height	30.0 cm
Package 3 Width	30.0 cm
Package 3 Length	40.0 cm
Package 3 Weight	2.916 kg

Offer Sustainability

REACh Regulation	REACh Declaration		
REACh free of SVHC	Yes		
EU RoHS Directive	Compliant EU RoHS Declaration		
Toxic heavy metal free	Yes		
Mercury free	Yes		
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)		
RoHS exemption information	Yes		
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins		

Recommended replacement(s)