

Product datasheet

Specifications



New Unica - electronic doorbell - 2 modules - beige

NU378644

Main

Range	New Unica
Device application	Signalling
Product or component type	Electronic doorbell
Device presentation	Mechanism
[Ue] rated operational voltage	230 V AC 50/60 Hz
Number of modules	2 modules
Fixing mode	Screws or claws
Colour tint	Beige (RAL 1013)

Complementary

Current consumption	14 mA
Type of setting	5 programmable melodies
Device mounting	Flush
Connections - terminals	Screw terminals
Acoustic level	70 dB/1m
Cable cross section	0.75...1.5 mm ² flexible cable 0.75...1.5 mm ² rigid cable
Connected auxiliaries	3 indicator lights connected in parallel 10 standard push-buttons connected in parallel
Material	Thermoplastic ABS-UV stabilised: mechanism rocker PC (polycarbonate) GF10 FR: casing
Standards	EN 62080 CE
Directives	2014/30/EU - electromagnetic compatibility 2014/35/EU - low voltage directive
Ambient air temperature for operation	15...30 °C
Ambient air temperature for storage	0...35 °C
Embedding depth	31 mm
Depth	50 mm
Width	45 mm
Height	45 mm

Net weight	0.046 kg
Resistance to chemical agents	Resistant to alcohol (70 %) Resistant to alcohol (96 %) Resistant to A-Lactic Acid Resistant to diluted quaternary ammonium Resistant to diluted bleach Resistant to diluted ammonia Resistant to soapy water Resistant to crystal cleaner Resistant to hydrogen peroxide 10 volumes Resistant to hexane

Environment

IK degree of protection	IK04
IP degree of protection	IP20

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.17 cm
Package 1 Width	6.3 cm
Package 1 Length	7.7 cm
Package 1 Weight	7.5 g
Unit Type of Package 2	S01
Number of Units in Package 2	9
Package 2 Height	15 cm
Package 2 Width	15 cm
Package 2 Length	40 cm
Package 2 Weight	268 g
Unit Type of Package 3	P06
Number of Units in Package 3	288
Package 3 Height	77 cm
Package 3 Width	80 cm
Package 3 Length	60 cm
Package 3 Weight	17.06 kg

Offer Sustainability

EU RoHS Directive	Under investigation
--------------------------	---------------------

Recommended replacement(s)