

Buzzer, New Unica, 2 modules, beige, 230V AC, clip-in, beige

NU378544

Main

Range	New Unica
Device application	Signalling
Product or component type	Buzzer
Aesthetic name	Unica (standard aesthetic)
Device presentation	Mechanism
[Ue] rated operational voltage	230 V AC 50/60 Hz
Number of modules	2 modules
Fixing mode	Clip-in
Colour tint	Beige (RAL 1013)

Complementary	
Current consumption	40 mA
Type of setting	Volume can be adjusted using a screw
Device mounting	Flush
Operating time	<= 30 ms
Connections - terminals	Screw terminals
Acoustic level	Between 76 and 80 dB
Cable cross section	0.751.5 mm² flexible cable 0.751.5 mm² rigid cable
Material	Thermoplastic ABS-UV stabilised: mechanism rocker PC (polycarbonate) GF10 FR: casing
Standards	EN 62080 CE
Directives	2014/35/EU - low voltage directive
Ambient air temperature for operation	1530 °C
Ambient air temperature for storage	035 °C
Embedding depth	31 mm
Depth	50 mm
Width	45 mm
Height	45 mm

Net weight	0.091 kg
Resistance to chemical agents	Resistant to alcohol (70 %) Resistant to alcohol (96 %) Resistant to A-Lactic Acid Resistant to diluted quaternary ammonium Resistant to diluted bleach Resistant to diluted ammonia Resistant to soapy water Resistant to crystal cleaner Resistant to hydrogen peroxide 10 volumes Resistant to hexane

Environment

IK degree of protection	IK04
IP degree of protection	IP20
Environmental characteristic	Oil Petrol Acetone Alcohol Bleach Window-cleaning fluid Liquid soap UV resistant

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.5 cm
Package 1 Width	4.5 cm
Package 1 Length	5.0 cm
Package 1 Weight	91.0 g
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	5.5 cm
Package 2 Width	14.0 cm
Package 2 Length	26.0 cm
Package 2 Weight	1.007 kg
Unit Type of Package 3	S02
Number of Units in Package 3	50
Package 3 Height	15.0 cm
Package 3 Width	30.0 cm
Package 3 Length	40.0 cm
Package 3 Weight	5.35 kg

Offer Sustainability

EU RoHS Directive Under investigation

Recommended replacement(s)