

# Product data sheet

Specifications



## New Unica - buzzer - 2 modules - aluminium

NU378530

### Main

Range	New Unica
Device application	Signalling
Product or component type	Buzzer
Device presentation	Mechanism
[Ue] rated operational voltage	230 V AC 50/60 Hz
Number of modules	2 modules
Fixing mode	Clip-in
Colour tint	Aluminium

### Complementary

Current consumption	40 mA
Type of setting	Volume can be adjusted using a screw
Device mounting	Flush
Operating time	<= 30 ms
Connections - terminals	Screw terminals
Acoustic level	Between 76 and 80 dB
Cable cross section	0.75...1.5 mm <sup>2</sup> flexible cable 0.75...1.5 mm <sup>2</sup> rigid cable
Material	Thermoplastic ABS-UV stabilised: mechanism rocker PC (polycarbonate) GF10 FR: casing
Standards	EN 62080 CE
Directives	2014/35/EU - low voltage directive
Ambient air temperature for operation	15...30 °C
Ambient air temperature for storage	0...35 °C
Embedding depth	31 mm
Depth	50 mm
Width	45 mm
Height	45 mm
Net weight	0.091 kg

<b>Resistance to chemical agents</b>	Resistant to alcohol (70 %) Resistant to alcohol (96 %) Resistant to A-Lactic Acid Resistant to diluted quaternary ammonium Resistant to diluted bleach Resistant to diluted ammonia Resistant to soapy water Resistant to crystal cleaner Resistant to hydrogen peroxide 10 volumes Resistant to hexane
--------------------------------------	---

## Environment

<b>IK degree of protection</b>	IK04
<b>IP degree of protection</b>	IP20

## Packing Units

<b>Unit Type of Package 1</b>	PCE
<b>Number of Units in Package 1</b>	1
<b>Package 1 Height</b>	4.500 cm
<b>Package 1 Width</b>	4.500 cm
<b>Package 1 Length</b>	5.000 cm
<b>Package 1 Weight</b>	50.000 g
<b>Unit Type of Package 2</b>	BB1
<b>Number of Units in Package 2</b>	10
<b>Package 2 Height</b>	6.000 cm
<b>Package 2 Width</b>	14.000 cm
<b>Package 2 Length</b>	26.000 cm
<b>Package 2 Weight</b>	572.000 g
<b>Unit Type of Package 3</b>	S03
<b>Number of Units in Package 3</b>	50
<b>Package 3 Height</b>	30.000 cm
<b>Package 3 Width</b>	30.000 cm
<b>Package 3 Length</b>	40.000 cm
<b>Package 3 Weight</b>	3.345 kg

## Offer Sustainability

<b>REACH Regulation</b>	<a href="#">REACH Declaration</a>
<b>REACH free of SVHC</b>	Yes
<b>EU RoHS Directive</b>	Compliant <a href="#">EU RoHS Declaration</a>
<b>Toxic heavy metal free</b>	Yes
<b>Mercury free</b>	Yes
<b>China RoHS Regulation</b>	<a href="#">China RoHS declaration</a> Pro-active China RoHS declaration (out of China RoHS legal scope)
<b>RoHS exemption information</b>	<a href="#">Yes</a>
<b>WEEE</b>	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

## Recommended replacement(s)