



New Unica - emergency light - 230 V AC - 2 modules

NU3776

Main

Range	New Unica
Product or component type	Emergency light
Device presentation	Mechanism
[Ue] rated operational voltage	230 V AC +/- 10 % at 50 Hz
Number of modules	2 modules
Fixing mode	Clip-in
Colour tint	White

Complementary

Battery and bulb cannot be replaced
Green
LED
400 h
25 cm: 45 lux
Screw terminals
<= 2 x 2.5 mm² for flexible cable(s) <= 2 x 2.5 mm² for rigid cable(s)
24 h
500 cycles
PC: mechanism cover PC (polycarbonate) GF10 FR: casing
EN 60598-2-22 CE
2014/35/EU - low voltage directive
545 °C
-550 °C
32 mm
43 mm
45 mm
45 mm

Net weight	0.085 kg
Resistance to chemical agents	Resistant to alcohol (70 %) Resistant to alcohol (96 %) Resistant to A-Lactic Acid Resistant to diluted quaternary ammonium Resistant to diluted bleach Resistant to diluted ammonia Resistant to soapy water Resistant to crystal cleaner Resistant to hydrogen peroxide 10 volumes Resistant to hexane
Environment	
IK degree of protection	IK03
IP degree of protection	IP2xC
Packing Units	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	6.4 cm
Package 1 Width	8.0 cm
Package 1 Length	8.6 cm
Package 1 Weight	80.0 g
Unit Type of Package 2	S02
Number of Units in Package 2	27
Package 2 Height	15.0 cm
Package 2 Width	30.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	2.464 kg
Offer Sustainability	
Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
RoHS exemption information	Yes

Recommended replacement(s)