

# Product data sheet

Specifications



Card switch, New Unica, mechanism, electronic, 8A, 2 modules, screw terminals, IP20, anthracite

NU354054

## Main

Range	New Unica
Product or component type	Card switch
Device application	Control
Device presentation	Mechanism
Colour tint	Anthracite

## Complementary

Technology type	Electronic
[Ue] rated operational voltage	230 V AC +/- 10 % at 50 Hz
Rated current	8 A
Load type	230 V AC incandescent lamp - 1470 W 230 V AC halogen lamp - 1470 W 230 V AC fan - 1470 W 230 V AC convector - 1470 W Low voltage halogen lamp with ferromagnetic transformer - 1000 VA Low voltage halogen lamp with electronic transformer - 1470 VA Fluorescent tube ferromagnetic ballast - 1470 VA Compact fluorescent lamp - 1470 W LED lamp - 1470 W Contactor
Actuator	Card 54 x 86 x 0.85 mm (maximum)
Number of modules	2 modules
Maximum number of switchings	50000 operations
Protection type	Thermal protection Overvoltage protection
Pilot light	Anthracite indicator lamp
Time delay	10 s
Marking	Vertical insertion pictogram
Connections - terminals	Screw terminals
Clamping connection capacity	<= 2 x 2.5 mm <sup>2</sup> for flexible cable(s) <= 2 x 2.5 mm <sup>2</sup> for rigid cable(s)
Fixing mode	Clip-in
Material	ABS (acrylonitrile butadiene-styrene): mechanism cover
Embedding depth	21 mm
Depth	40.7 mm

<b>Width</b>	45 mm
<b>Height</b>	45 mm
<b>Net weight</b>	0.045 kg

## Environment

<b>IP degree of protection</b>	IP20
<b>IK degree of protection</b>	IK01
<b>Ambient air temperature for operation</b>	5...30 °C
<b>Ambient air temperature for storage</b>	-20...60 °C
<b>Environmental characteristic</b>	Alcohol Acetone Petrol Liquid soap Window-cleaning fluid Oil UV resistant Bleach
<b>Standards</b>	EN 60669-1

## Packing Units

<b>Unit Type of Package 1</b>	PCE
<b>Number of Units in Package 1</b>	1
<b>Package 1 Height</b>	6.3 cm
<b>Package 1 Width</b>	7.7 cm
<b>Package 1 Length</b>	8.6 cm
<b>Package 1 Weight</b>	77.7 g

## Offer Sustainability

<b>EU RoHS Directive</b>	Under investigation
--------------------------	---------------------

## Recommended replacement(s)