

Product datasheet

Specifications



Bluetooth audio receiver, New Unica, mechanism, 15/16V DC, 265V AC, anthracite

NU360154

Main

Range	New Unica
Product or component type	Audio receiver
Device presentation	Mechanism

Complementary

Device mounting	Flush
Fixing mode	Screws Claws
Device composition	1 audio receiver 1 power supply
Communication network type	Bluetooth (10 m)
Connector type	Jack (3.5 mm), 62 Ohm
Colour tint	Anthracite (RAL 7021)
[Ue] rated operational voltage	Audio receiver: 15/16 V DC Power supply: 265 V AC 47...63 Hz
Current consumption	4.5...100 mA with bluetooth 4.5...75 mA with jack
Maximum power consumption in W	12 W for power supply
Input voltage	100 mVrms with jack
Output voltage	15 V DC power supply:
Output current	800 mA power supply
Nominal output power	0 W 2.5 W 5 W 1.5 W
Left/Right channel separation	58 dB
Bandwidth	45...20000 Hz
Signal to noise ratio	84 dB
Bluetooth identification number	0...9999
Transmission frequency	2.4 GHz
RF Power transmitter	7 dBm
Connections - terminals	Screw terminals

Material	ABS (acrylonitrile butadiene-styrene): centre plate
Ambient air temperature for operation	0...40 °C
Ambient air temperature for storage	0...60 °C
Net weight	0.24 kg

Environment

IP degree of protection	IP20
IK degree of protection	IK01

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.500 cm
Package 1 Width	10.500 cm
Package 1 Length	14.500 cm
Package 1 Weight	107 g
Unit Type of Package 2	S03
Number of Units in Package 2	30
Package 2 Height	30.000 cm
Package 2 Width	30.000 cm
Package 2 Length	40.000 cm
Package 2 Weight	7.132 kg

Offer Sustainability

REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
RoHS exemption information	Yes

Recommended replacement(s)