Product data sheet

Specifications



Bluetouh audio receiver, New Unica, mechanism, 15/16V DC, 265V AC, white

NU360118

viain	

Range	New Unica
Product or component type	Audio receiver
Device presentation	Mechanism

Complementary	
Device mounting	Flush
Fixing mode	Claws Screws
Device composition	1 audio receiver 1 power supply
Communication network type	Bluetooth (10 m)
Connector type	Jack (3.5 mm), 62 Ohm
Colour tint	White (RAL 9003)
[Ue] rated operational voltage	Audio receiver: 15/16 V DC Power supply: 265 V AC 4763 Hz
Current consumption	4.5100 mA with bluetooth 4.575 mA with jack
Maximum power consumption in W	12 W for power supply
Input voltage	100 mVrms with jack
Output voltage	15 V DC power supply:
Output current	800 mA power supply
Nominal output power	0 W 1.5 W 2.5 W 5 W
Left/Right channel separation	58 dB
Bandwidth	4520000 Hz
Signal to noise ratio	84 dB
Bluetooth identifi cation number	09999
Transmission frequency	2.4 GHz
RF Power transmitter	7 dBm
Connections - terminals	Screw terminals

Material	ABS (acrylonitrile butadiene-styrene): centre plate
Ambient air temperature for operation	040 °C
Ambient air temperature for storage	060 °C
Net weight	0.24 kg
Environment	
IP degree of protection	IP20
IK degree of protection	IK01
Packing Units	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5 cm
Package 1 Width	10 cm
Package 1 Length	14 cm
Package 1 Weight	107 g
Unit Type of Package 2	BB1
Number of Units in Package 2	1
Package 2 Height	5 cm
Package 2 Width	10 cm
Package 2 Length	14 cm
Package 2 Weight	107 g
Unit Type of Package 3	S04
Number of Units in Package 3	67
Package 3 Height	30 cm
Package 3 Width	40 cm
Package 3 Length	60 cm
Package 3 Weight	7.872 kg
Offer Sustainability	
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
RoHS exemption information	Yes

Recommended replacement(s)

Feb 28, 2023