

TV socket, New Unica, mechanism, 1 module, F-Type, painted, IP2xC, anthracite

NU346854

Main

Range	New Unica
Product or component type	TV socket
Device application	Connection
Device presentation	Mechanism
Colour tint	Anthracite (RAL 7021)

Complementary

TV connector	F connectors
Number of modules	1 module
Material	Thermoplastic ABS-UV stabilised: mechanism cover
Surface finish	Matt
Surface treatment	Painted
Fixing mode	Clip-in
Depth	35 mm
Width	22.5 mm
Height	45 mm
Embedding depth	18 mm
Net weight	0.013 kg
Ambient air temperature for operation	545 °C
Ambient air temperature for storage	-550 °C

Resistance to chemical agents Resistant to alcohol (70 %)

Resistant to alcohol (96 %)

Resistant to A-Lactic Acid

Resistant to diluted quaternary ammonium

Resistant to diluted bleach Resistant to diluted ammonia Resistant to soapy water Resistant to crystal cleaner

Resistant to hydrogen peroxide 10 volumes

Resistant to hexane

Environment

IK degree of protection IK04

IP degree of protection	IP2xC
Packing Units	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4 cm
Package 1 Width	2.2 cm
Package 1 Length	4.5 cm
Package 1 Weight	11 g
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	6 cm
Package 2 Width	14 cm
Package 2 Length	26 cm
Package 2 Weight	187 g
Unit Type of Package 3	S01
Number of Units in Package 3	20
Package 3 Height	15 cm
Package 3 Width	15 cm
Package 3 Length	40 cm
Package 3 Weight	612 g
Offer Sustainability	
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes

Pro-active China RoHS declaration (out of China RoHS legal scope)

The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Recommended replacement(s)

China RoHS Regulation

WEEE

RoHS exemption information

China RoHS declaration

Yes