



New Unica - USB 2.0 data connector - 1 module - aluminium

NU342930

Range	New Unica
Product or component type	USB connector
Connector type	USB 2.0
Electrical circuit type	Data
Device presentation	Mechanism
Colour tint	Aluminium
Type of packing	Flow-pack

Complementary

Socket number	1
Fixing mode	Clip-in
Number of modules	1 module
Surface finish	Matt
Quantity per set	Set of 10
Connections - terminals	Screw terminals
Clamping connection capacity	<= 1.5 mm² for flexible cable(s) <= 1.5 mm² for rigid cable(s)
Wire stripping length	8 mm
Material	Thermoplastic ABS-UV stabilised: centre plate PC (polycarbonate) GF10 FR: casing
Height	45 mm
Width	22.5 mm
Depth	28 mm
Embedding depth	19.7 mm
Net weight	0.014 kg
Directives	2014/30/EU - electromagnetic compatibility
Resistance to chemical agents	Resistant to alcohol (70 %)

Resistant to alcohol (96 %)

Resistant to A-Lactic Acid

Resistant to diluted quaternary ammonium

Resistant to diluted bleach Resistant to diluted ammonia Resistant to soapy water Resistant to crystal cleaner

Resistant to hydrogen peroxide 10 volumes

_								٠
⊢	nı	/1	ro	n	m	Δ	n	t
_		v				_		_

Ambient air temperature for storage	-550 °C
Ambient air temperature for operation	545 °C
Standards	EN 62680-2-1 EN 61000-6-3 EN 61000-6-1
IP degree of protection	IP2xC
IK degree of protection	IK02

Packing Units

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
China RoHS Regulation RoHS exemption information	
	Pro-active China RoHS declaration (out of China RoHS legal scope)

WEEE

The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Recommended replacement(s)