

Product datasheet

Specifications



New Unica - USB charger 1 A - 1 module - type A - beige

NU342844

Main

| | |
|---------------------------|-------------|
| Range | New Unica |
| Product or component type | USB charger |
| Device presentation | Mechanism |

Complementary

| | |
|---------------------------------------|---|
| Device application | Charger |
| Device mounting | Flush |
| Number of modules | 1 module |
| Type of USB power supply | USB type A |
| Colour tint | Beige (RAL 1013) |
| [Ue] rated operational voltage | 100...240 V AC 50/60 Hz |
| Nominal output power | 5 W |
| Input power | 7.5 W |
| Socket number | 1 |
| Integrated connection type | 1 USB type A 5 V DC, maximum load current: 1 A |
| Material | PC (polycarbonate) GF10 FR: casing PC (polycarbonate) GF10 FR: internal cover Thermoplastic ABS-UV stabilised: centre plate |
| Protection type | Short-circuit protection |
| Number of terminals | 2 screw terminals |
| Shape of screw head | Pozidriv No 1 |
| Clamping connection capacity | 1.5...2.5 mm ² for rigid cable(s) 1.5...2.5 mm ² for flexible cable(s) |
| Wire stripping length | 8 mm |
| Product compatibility | All devices fulfilling the EN 62684 standard |
| Fixing mode | Clip-in |
| Type of packing | Flow-pack |
| Ambient air temperature for operation | 5...45 °C |
| Ambient air temperature for storage | -5...50 °C |
| Standards | IEC 62368-1 |

EN 61000-6-1
EN 61000-6-3
IEC 62680-3

| | |
|--------------------------------------|---|
| Height | 45 mm |
| Width | 22.5 mm |
| Depth | 42 mm |
| Embedding depth | 30.8 mm |
| Net weight | 0.03 kg |
| Resistance to chemical agents | Resistant to alcohol (70 %) Resistant to alcohol (96 %) Resistant to A-Lactic Acid Resistant to diluted quaternary ammonium Resistant to diluted bleach Resistant to diluted ammonia Resistant to soapy water Resistant to crystal cleaner Resistant to hydrogen peroxide 10 volumes Resistant to hexane |

Environment

| | |
|------------------------------------|----------|
| Electrical insulation class | Class II |
| IK degree of protection | IK04 |
| IP degree of protection | IP2xC |

Packing Units

| | |
|-------------------------------------|----------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 3.4 cm |
| Package 1 Width | 15.9 cm |
| Package 1 Length | 8.7 cm |
| Package 1 Weight | 32.0 g |
| Unit Type of Package 2 | S02 |
| Number of Units in Package 2 | 50 |
| Package 2 Height | 15.0 cm |
| Package 2 Width | 30.0 cm |
| Package 2 Length | 40.0 cm |
| Package 2 Weight | 1.915 kg |
| Unit Type of Package 3 | P06 |
| Number of Units in Package 3 | 800 |
| Package 3 Height | 77.0 cm |
| Package 3 Width | 80.0 cm |
| Package 3 Length | 60.0 cm |
| Package 3 Weight | 39.14 kg |

Offer Sustainability

| | |
|------------------------------|---|
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Mercury free | Yes |
| China RoHS Regulation | China RoHS declaration Product out of China RoHS scope. Substance declaration for your information |

RoHS exemption information Yes

Recommended replacement(s)