Main Range



Power supply

Socket-outlet

Mechanism

1

2P + E

British

Displaced earth

Device application

Device presentation

Socket number

Outlet standard

Product or component type

Outlet poles configuration

Outlet standard description

| Complementary | |
|--------------------------------|--|
| Cover type | With shutter |
| Device mounting | Flush |
| Rated current | 15 A |
| [Ue] rated operational voltage | 250 V |
| Network type | AC |
| Network frequency | 50/60 Hz |
| Number of modules | 2 modules |
| Fixing mode | Clip-in |
| Colour tint | Anthracite (RAL 7021) |
| Connections - terminals | Screw terminals |
| Cable cross section | 04 mm² cable(s), 2 - cable stiffness: flexible 04 mm² - cable stiffness: rigid |
| Minimum load breaking capacity | 100 operations 1.25 In and 1.1 Un, cos phi = 0.6 |
| Electrical durability | 10000 cycles, cos phi = 0.8 |
| Insulation resistance | > 5 MOhm at 500 V |
| Dielectric strength | 2000 V |
| Material | PC: mechanism cover PC (polycarbonate) GF10 FR: casing |
| Surface finish | Painted |
| Quantity per set | Set of 1 flow-pack |

| Standards | IEC 60884-1 |
|-------------------------------|--|
| Embedding depth | 30 mm |
| Depth | 33 mm |
| Width | 45 mm |
| Height | 45 mm |
| Net weight | 0.0389 kg |
| Surface treatment | Painted |
| Resistance to chemical agents | Resistant to alcohol (70 %) Resistant to alcohol (96 %) Resistant to A-Lactic Acid Resistant to diluted quaternary ammonium Resistant to diluted bleach Resistant to diluted ammonia Resistant to soapy water Resistant to crystal cleaner Resistant to hydrogen peroxide 10 volumes Resistant to hexane |

Environment

| Ambient air temperature for operation | -535 °C |
|---------------------------------------|--|
| Ambient air temperature for storage | -550 °C |
| IK degree of protection | IK01 |
| IP degree of protection | IP21D |
| Environmental characteristic | Alcohol Acetone Oil UV resistant Window-cleaning fluid Petrol Bleach Liquid soap |

Packing Units

| r doming office | |
|------------------------------|----------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 3.4 cm |
| Package 1 Width | 4.5 cm |
| Package 1 Length | 4.5 cm |
| Package 1 Weight | 39.2 g |
| Unit Type of Package 2 | BB1 |
| Number of Units in Package 2 | 10 |
| Package 2 Height | 5.5 cm |
| Package 2 Width | 14.0 cm |
| Package 2 Length | 26.0 cm |
| Package 2 Weight | 489.0 g |
| Unit Type of Package 3 | S03 |
| Number of Units in Package 3 | 100 |
| Package 3 Height | 30.0 cm |
| Package 3 Width | 30.0 cm |
| Package 3 Length | 40.0 cm |
| Package 3 Weight | 5.331 kg |
| | |

Offer Sustainability

EU RoHS Directive

Under investigation

Recommended replacement(s)