Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

New Unica - Double USB Quick Charge A+C - 18W





| ſ | Иa | aiı | n |
|---|----|-----|---|
| Ξ | | | |

| Range | New Unica |
|---------------------------|-------------|
| Product or component type | USB charger |
| Device presentation | Mechanism |
| Condition of use | Indoor |

| Complementary | |
|---------------------------------------|--|
| Device application | Charger |
| Device mounting | Flush |
| Number of modules | 2 modules |
| Type of USB power supply | USB type A + C |
| Colour tint | Anthracite (RAL 7021) |
| Surface finish | Painted powder coated |
| [Ue] rated operational voltage | 100240 V AC 50/60 Hz |
| Power consumption in W | 0.1 W |
| Nominal output power | 18 W |
| Service life in hours | 30000 h 18 W |
| Socket number | 2 |
| Integrated connection type | 1 USB type A 5 V DC, maximum load current: 1 A 1 USB type C 5 V DC, maximum load current: 2.4 A |
| Material | Plastic: housing |
| Protection type | Short-circuit Surge Overheating Overvoltage Overcurrent |
| Number of terminals | 2 screw terminals |
| Shape of screw head | Pozidriv No 1 |
| Clamping connection capacity | 2 x 0.752 x 2.5 mm² for rigid cable(s) 2 x 0.752 x 2.5 mm² for flexible cable(s) |
| Wire stripping length | 7 mm |
| Fixing mode | Clip-in |
| Ambient air temperature for operation | 040 °C |

| Height | 45 mm |
|-------------------------------|--|
| Width | 45 mm |
| Depth | 40 mm |
| Embedding depth | 32 mm |
| Resistance to chemical agents | Resistant to alcohol (70 %) Resistant to alcohol (96 %) Resistant to A-Lactic Acid Resistant to diluted quaternary ammonium Resistant to diluted bleach Resistant to diluted ammonia Resistant to soapy water Resistant to crystal cleaner Resistant to hydrogen peroxide 10 volumes Resistant to hexane |

Environment

| Electrical insulation class | Class II |
|-----------------------------|----------|
| IK degree of protection | IK04 |
| IP degree of protection | IP20 |

Packing Units

| Unit Type of Package 1 | PCE |
|------------------------------|-----------|
| Number of Units in Package 1 | 1 |
| Package 1 Height | 7.700 cm |
| Package 1 Width | 9.500 cm |
| Package 1 Length | 9.500 cm |
| Package 1 Weight | 113.000 g |
| Unit Type of Package 2 | S02 |
| Number of Units in Package 2 | 9 |
| Package 2 Height | 15.000 cm |
| Package 2 Width | 30.000 cm |
| Package 2 Length | 40.000 cm |
| Package 2 Weight | 1.243 kg |
| Unit Type of Package 3 | P06 |
| Number of Units in Package 3 | 144 |
| Package 3 Height | 77.000 cm |
| Package 3 Width | 80.000 cm |
| Package 3 Length | 60.000 cm |
| Package 3 Weight | 24.272 kg |

Offer Sustainability

EU RoHS Directive Under investigation

Recommended replacement(s)