# **Product data sheet**

Specifications



## New Unica - Double USB Quick Charge A+C - 18W

NU301918

***

Range	New Unica
Product or component type	USB charger
Device presentation	Mechanism
Condition of use	Indoor

Complementary	
Device application	Charger
Device mounting	Flush
Number of modules	2 modules
Type of USB power supply	USB type A + C
Colour tint	White (RAL 9003)
Surface finish	Glossy
[Ue] rated operational voltage	100240 V AC 50/60 Hz
Power consumption in W	0.1 W
Nominal output power	18 W
Service life in hours	30000 h 18 W
Socket number	2
Integrated connection type	1 USB type A 5 V DC, maximum load current: 1 A 1 USB type C 5 V DC, maximum load current: 2.4 A
Material	Plastic: housing
Protection type	Short-circuit Surge Overheating Overvoltage Overcurrent
Number of terminals	2 screw terminals
Shape of screw head	Pozidriv No 1
Clamping connection capacity	2 x 0.752 x 2.5 mm² for rigid cable(s) 2 x 0.752 x 2.5 mm² for flexible cable(s)
Wire stripping length	7 mm
Fixing mode	Clip-in
Ambient air temperature for operation	040 °C

Height	45 mm
Width	45 mm
Depth	40 mm
Embedding depth	32 mm
Resistance to chemical agents	Resistant to alcohol (70 %) Resistant to alcohol (96 %) Resistant to A-Lactic Acid Resistant to diluted quaternary ammonium Resistant to diluted bleach Resistant to diluted ammonia Resistant to soapy water Resistant to crystal cleaner Resistant to hydrogen peroxide 10 volumes Resistant to hexane

#### **Environment**

Electrical insulation class	Class II
IK degree of protection	IK04
IP degree of protection	IP20

### **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7.7 cm
Package 1 Width	9.5 cm
Package 1 Length	9.5 cm
Package 1 Weight	113 g
Unit Type of Package 2	S03
Number of Units in Package 2	27
Package 2 Height	30 cm
Package 2 Width	30 cm
Package 2 Length	40 cm
Package 2 Weight	3.427 kg
Package 3 Height	77 cm

### Offer Sustainability

EU RoHS Directive Under investigation

Recommended replacement(s)