

#### **URBAN SUNNY**

| Driver Origin |       |      |      | Lifetime |  |  |
|---------------|-------|------|------|----------|--|--|
| MW            | Taiwa | CREE | USA  | 50000    |  |  |
|               | n     |      | 0.07 |          |  |  |

# Product Description

A collection of urban lighting units provided with many patents and independentintellectual properties and many advanced technologies.

Treated with special techniqueto ensure excellent radiation performance

#### Basic Data

| Material        | Steel & Aluminum       |  |  |  |
|-----------------|------------------------|--|--|--|
| Finishing       | Electrostatic Painting |  |  |  |
| Optics          |                        |  |  |  |
| Weight          | 75 kg                  |  |  |  |
| IP              | 65                     |  |  |  |
| IK              | 08                     |  |  |  |
| Suspension      | Pole Mounted           |  |  |  |
| Additional Data |                        |  |  |  |


## Specifications


| Art No.   | WAT | CCT  | CRI | LED | Ang | e TL | Ø |  |
|-----------|-----|------|-----|-----|-----|------|---|--|
| 75505-PL- | 45  | 3000 | 75  | 42  | 97  | 3939 | _ |  |
| 75506-PL- | 45  | 5000 | 75  | 42  | 97  | 4221 | _ |  |

#### **Dimensions**



### Light Distribution





All Luminaries are electrical tested & protection tested according to the standard (IEC 598)