

# Product datasheet

Specifications



## Blind/switch actuator, SpaceLogic KNX, 2 gang, flush mounted, 3 binary inputs, KNX Secure

MTN6003-0012

### Main

Range of product	SpaceLogic KNX
Product or component type	Blind switch actuator
Operating mode	KNX bus system
Bus type	KNX
Rated input	Signal voltage (SELV): 3 x binary

### Complementary

Mounting support	Flush
[Ue] rated operational voltage	230 V AC 50/60 Hz
[In] rated current	16 A
Number of outputs	2
Load type	Motor: , 230 V AC Incandescent lamp: <= 2500 W, 230 V AC High voltage halogen lamp: <= 2500 W, 230 V AC LED lamp: <= 400 W, 230 V AC Capacitive: , 16 A, 140 µF, 230 V AC Resistive load: 2500 W
Maximum cable length	10 m for input
Width	48 mm
Height	28 mm
Depth	50 mm

### Environment

IP degree of protection	IP20
Ambient air temperature for operation	-5...45 °C

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	6.2 cm
Package 1 Width	7.5 cm
Package 1 Length	7.5 cm

Package 1 Weight	121.0 g
Unit Type of Package 2	S03
Number of Units in Package 2	60
Package 2 Height	30 cm
Package 2 Width	30 cm
Package 2 Length	40 cm
Package 2 Weight	7.754 kg
Package 3 Height	30 cm

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS declaration</a> Pro-active China RoHS declaration (out of China RoHS legal scope)
RoHS exemption information	Yes
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End of Life Information</a>

## Contractual warranty

Warranty	18 months
----------	-----------

## Recommended replacement(s)